Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated

Arrival Name			Number	STAR Computer Code		Superseded Number			Dated	Effective Date
OAKES (RNAV)			THREE	OAKES.OAKES3	TWO			10/15/2015		
RANSITION ROUTE	ES:									
Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	MAA	Crossing Al	titudes / Fixes
MRLET	MRLET.OAKES3	MRLET	MRLET							
			POYSN	178.91	51.55	FL200	13100			
			OAKES	194.75	27.80	16000	9400		BETWEEN FL	240 AND FL320
RPARK	RPARK.OAKES3	RPARK	RPARK							
			MOLLA	245.74	46.50	FL200	14700			
			OAKES	245.02	30.92	16000	11400		BETWEEN FL	240 AND FL320
RUSME	RUSME.OAKES3	RUSME	RUSME							
			OAKES	266.63	136.79	FL200	16500		BETWEEN FL	240 AND FL320

ARRIVAL ROUTE DESCRIPTION:

OAK: FROM OAKES ON TRACK 244.10/24.66 TO CROSS GRUDG BETWEEN FL200 AND FL230 AND AT 260 KIAS, THEN ON TRACK 243.68/9.93 TO CROSS BANND BETWEEN 17000 AND FL190.

LANDING OAK RWY 12: FROM BANND ON TRACK 277.38/16.54 TO CROSS SULRR BETWEEN 12000 AND 13000 AND AT 250 KIAS, THEN ON TRACK 263.76/16.78 TO CROSS KEENR AT 7000, THEN ON TRACK 261.83/10.66 TO CROSS LOHGN AT 6000 AND AT 200 KIAS, THEN ON TRACK 260.76/4.00 TO CROSS WHYEE AT OR ABOVE 5000, THEN ON TRACK 260.79/5.00 TO CROSS HIRMO AT 4000, THEN ON TRACK 260.79. EXPECT RNAV (RNP) Z RWY 12 APPROACH OR RADAR VECTORS TO FINAL APPROACH COURSE.

LANDING OAK RWY 28L/R, 30: FROM BANND ON TRACK 243.67/12.94 TO TOOOL, THEN ON TRACK 237.20/18.10 TO CROSS FFIST BETWEEN 7000 AND 9000 AND AT 200 KIAS. EXPECT ILS OR RNAV APPROACH RWY 28L/R, 30 APPROACH.

LANDING HWD: FROM OAKES ON TRACK 244.10/24.66 TO CROSS GRUDG BETWEEN FL200 AND FL230 AND AT 260 KIAS. THEN ON TRACK 243.68/9.93 TO CROSS BANND BETWEEN 17000 AND FL190, THEN ON TRACK 243.67/12.94 TO TOOOL, THEN ON TRACK 237.20/18.10 TO CROSS FFIST BETWEEN 7000 AND 9000 AND AT 200 KIAS, THEN ON TRACK 180.91/6.09 TO CROSS NORCL AT 7000, THEN ON TRACK 237.00. EXPECT RADAR VECTORS TO FINAL APPROACH COURSE.

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

NOTE: EXPECT WEST TRANSITION UNLESS OTHERWISE INDICATED.

FIXES AND/OR HOLDING PATTERNS:

CHART HOLDING AT RPARK: HOLD NE, RT, 245.74 INBOUND, 10 NM LEGS. CHART HOLDING AT GRUDG: HOLD NE, RT, 244.10 INBOUND, 10 NM LEGS. CHART: TATOO

COMMUNICATIONS:

CHART: ZOA, OAKLAND GND CON, OAKLAND ATCT, HAYWARD GND CON, HAYWARD ATCT.

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.

	Cellings are in reet above airport eleva	tion. Distances are in nautical miles. Visibilities are in si	atule miles of feet RVR unless otherwise indicated.		
Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
OAKES (RNAV)	THREE	OAKES.OAKES3	TWO	10/15/2015	
AIRPORTS SERVED:					
AIRPORT ID		CITY	<u>ST/</u>	ATE	
OAK		OAKLAND	C	A	
HWD		HAYWARD	C	A	

LOST COMMUNICATIONS PREFERENCES:

REMARKS:

ROC REDUCTION TAKEN FOR RWY 12 TRANSITION SEGMENT KEENR-LOHGN SEGMENT.

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: SAT (RNP 2.0) MAG VAR: OAK 14E/2015. CHART AT HIRMO TERMINUS: OAK LDG RWY 12 CHART AT FFIST TERMINUS: OAK LDG RWY 28L/R, 30 CHART AT NORCL TERMINUS: LDG HWD

FLIGHT INSPECTED BY: JOSEPH R JAQUISH	ORGANIZATION: AJF	DATE: 01/22/2025	Flight Inspected Signature:	ALLAN WILL Apr 11, 2025	
DEVELOPED BY: TODD DAMRON	AJV-A423	10/02/2024	Developed By Signature:	Digitally signed by TODD V DAMRON	
APPROVED BY: ALLAN WILL (MANAGER)	AJV-A423		Approved By Signature:	Feb 10, 2025 Digitally signed by ALLAN WILL	
01411050				Apr 11, 2025	

CHANGES:

1. CHANGED SPEED RESTRICTION AT GRUDG FROM 280 KIAS TO 260 KIAS.

2. CHANGED ALTITUDE RESTRICTION AT BANND FROM AT OR BELOW FL190 TO 17000BFL190.

3. REMOVED ALTITUDE AND SPEED RESTRICTIONS FROM TOOOL.

4. MOVED TOOOL 2.7 NM SOUTHWEST.

5. ADDED SPEED RESTRICTION AT FFIST AT 210 KIAS.

6. REMOVED EVOLV AND BBUBB FROM RWY 28L/R TRANSITION.

7. REMOVED PRFCT AND PARBB FROM RWY 30 TRANSITION.

8. ADDED CHART NOTE TO EXPECT WEST TRANSITION UNLESS OTHERWISE INDICATED.

9. ADDED HOLDING AT RPARK AND GRUDG.



Digitally signed by

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
OAKES (RNAV)	THREE	OAKES.OAKES3	TWO	10/15/2015	

10. DELETED INSLO.

11. DELETED MONOH TRANSITION AND ADDED RPARK TRANSITION.

12. ADDED HWD SATELLITE AIRPORT WITH ASSOCIATED TRANSITION DATA TO STAR.

13. COMBINED AND REVISED RWY 28L/R, 30 FIXES AND TRANSITIONS.

14. ADDED ROC REDUCTION REMARK.

15. UPDATED ENROUTE MOCA VALUES.

16. REMOVED MEA/MOCA VALUES FROM ARRIVAL ROUTE DESCRIPTION.

17. AIRPORTS SERVED: REMOVED NAME AND ADDED IDENT.

REASONS:

1-2: ATC AND INDUSTRY REQUEST.

3: TOOOL RESTRICTIONS NO LONGER NEEDED TO PASS REFERENCE SOFTWARE.

4: TOOOL MOVED TO AVOID CA-74 SKYDIVING JUMP AIRSPACE.

5-13. ATC AND INDUSTRY REQUESTED.

14. ROC REDUCTION TAKEN TO MAINTAIN CARDINAL ALTITUDE.

15. MOCA VALUES UPDATED WITH NEW REFERENCE SOFTWARE AND AT ATC REQUEST.

16. REMOVED TO MEET CRITERIA.


17. IAW 8260.19J, 4-5-12G.

01/14/25: THIS IS AN UPDATED COPY OF THE FORM DEVELOPED ON 10/2/24.


1. SPEED REESTRICTION 210 CHANGED TO 200 KIAS AT FIX FFIST/LOHGN.

Page 3 of 4

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.



Graphic Depiction 1



FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE STAR (DATA RECORD)

Arrival Name OAKES (RNAV)			mber IREE	S	TAR Comp OAKES.O		•	ded NumberDatedTWO10/15/2015		Effective Date
IX/NAVAID	LAT/LONG	<u> </u>	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS	
En Route Transition										
MRLET	390737.20N / 1194931.20W	Y		IF					MRLET.OAKES3	
POYSN	381718.33N / 1200409.08W	Y	FB	TF	192.91	51.55				
OAKES	375252.93N / 1202102.50W	Y	FB	TF	208.75	27.80	FL240BFL320	AT 280K		
En Route Transition										
RPARK	380724.91N / 1184449.79W	Y		IF					RPARK.OAKES3	
MOLLA	375852.98N / 1194242.06W	Y	FB	TF	259.74	46.50				
OAKES	375252.93N / 1202102.50W	Y	FB	TF	259.02	30.92	FL240BFL320	AT 280K		
En Route Transition										
RUSME	372939.00N / 1173112.00W	Y		IF					RUSME.OAKES3	
OAKES	375252.93N / 1202102.50W	Y	FB	TF	280.63	136.79	FL240BFL320	AT 280K		
Common Route										
OAKES	375252.93N / 1202102.50W	Y		IF			FL240BFL320	AT 280K	OAKES.OAKES3	
GRUDG	374743.55N / 1205128.85W	Y	FB	TF	258.10	24.66	FL200BFL230	AT 260K		
BANND	374535.69N / 1210342.58W	Y	FB	TF	257.68	09.93	17000BFL190			
Common Route										
OAKES	375252.93N / 1202102.50W	Y		IF			FL240BFL320	AT 280K	OAKES.OAKES3	
GRUDG	374743.55N / 1205128.85W	Y	FB	TF	258.10	24.66	FL200BFL230	AT 260K		
BANND	374535.69N / 1210342.58W	Y	FB	TF	257.68	09.93	17000BFL190			
TOOOL	374248.74N / 1211938.18W	Y	FB	TF	257.67	12.94				
FFIST	373656.40N / 1214112.38W	Y	FB	TF	251.20	18.10	7000B9000	AT 200K		
NORCL	373102.66N / 1214310.60W	Y	FO	TF	194.91	06.09	AT 7000			
KHWD				FM	251.00					
Runway Transition										
BANND	374535.69N / 1210342.58W	Y		IF			17000BFL190		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	ALITL

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE STAR (DATA RECORD)

Arrival Name OAKES (RNAV)			mber IREE		STAR Comp OAKES.O/		•	rseded Number Dated TWO 10/15/2015		Effective Date
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS	
SULRR	375136.32N / 1212309.33W	Y	FB	TF	291.38	16.54	12000B13000	AT 250K		
KEENR	375350.51N / 1214409.87W	Y	FB	TF	277.76	16.78	AT 7000			
LOHGN	375454.79N / 1215733.96W	Y	FB	TF	275.83	10.66	AT 6000	AT 200K		
WHYEE	375514.63N / 1220236.22W	Y	FB	TF	274.76	04.00	AT/ABOVE 5000			
HIRMO	375539.54N / 1220854.06W	Y	FO	TF	274.79	05.00	AT 4000			
KOAK:RWY 12		-		FM	274.79					
Runway Transition										
BANND	374535.69N / 1210342.58W	Y		IF			17000BFL190			
TOOOL	374248.74N / 1211938.18W	Y	FB	TF	257.67	12.94				
FFIST	373656.40N / 1214112.38W	Y	FB	TF	251.20	18.10	7000B9000	AT 200K		
KOAK:RWY 28L,RWY 28R,RWY 30										