

Print

Project Name: BPG

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-02-25 13:33:29.419918

Status: Verified

!FDC 6/3352 BPG IAP BIG SPRING/MC MAHON-WRINKLE, BIG SPRING, TX. RNAV (GPS) RWY 35, AMDT 1A... LNAV CAT C VISIBILITY 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.45 NM TO RW35. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MAF ALTIMETER SETTING: INCREASE LPV DA TO 2943 FEET; INCREASE LNAV/VNAV DA TO 3109 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 140 FEET AND LNAV VISIBILITY CAT C 3/8 SM AND LNAV VISIBILITY CAT D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING MAF ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 35, AMDT 1B. 2602251333-PERM

Digitally signed by
CASEY D HILL
Mar 04, 2026

