

[Print](#)

Project Name: SLG

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-16 17:56:21.370878

Status: Verified

!FDC 6/4918 SLG IAP SMITH FLD, SILOAM SPRINGS, AR. RNAV (GPS) RWY 36, ORIG-A... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP NOTE TO READ: CHART VDP AT 1.38 NM TO RW36. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE XNA ALTIMETER SETTING: INCREASE LPV DA TO 1469 FEET; INCREASE LNAV/VNAV DA TO 1587 FEET; INCREASE ALL MDAS 40 FEET. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING XNA ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NOTE TO READ: RWY 36 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 36, ORIG-B. 2604161756-PERM

Digitally signed by

CASEY D HILL

Apr 24, 2026

