

Print

Project Name: HYA

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Digitally signed by

Last Updated At: 2026-03-20 13:20:08.207991

RAKE MCGRAW

Mar 27, 2026

Status: Verified

6/4470

!FDC X/XXXX HYA IAP CAPE COD GATEWAY, HYANNIS, MA. RNAV (GPS) RWY 24, AMDT 1C... LNAV CATS C/D VISIBILITY RVR 5500. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CQX ALTIMETER SETTING: INCREASE LPV DA TO 350 FEET; INCREASE LNAV/VNAV DA TO 473 FEET; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CATS C/D TO RVR 6000 AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING CQX ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. DELETE NOTE FOR INOPERATIVE ALS WHEN USING CHATHAM ALTIMETER SETTING, INCREASE LNAV/VNAV VISIBILITY ALL CATS TO 1 1/4 SM. THIS IS RNAV (GPS) RWY 24, AMDT 1D. 2603201320-PERM

