

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>	<u>AMDT NO</u>	<u>ACTUAL EFFECTIVE DATE</u>
DUA	DURANT	OK	2	

TAKEOFF MINIMUMS:

RWY 17: STANDARD.

RWY 35: 400-3 OR STANDARD WITH MINIMUM CLIMB OF 205 FT/NM TO 1200 OR STANDARD AND CROSSING DER 8 FT ABOVE DER ELEV CLEARS TAKEOFF MINIMUMS OBSTACLES.

TEXTUAL DEPARTURE PROCEDURES:

VISUAL CLIMB OVER AIRPORT:

TAKEOFF OBSTACLE NOTES:

RWY 35, TAKEOFF MINIMUMS OBSTACLES: TOWER 2.4 NM FROM DER, LEFT OF CENTERLINE, UP TO 1077 FT MSL, 378 FT ABOVE DER. CROSSING DER 8 FT ABOVE DER ELEV CLEARS TAKEOFF MINIMUMS OBSTACLES.

CONTROLLING OBSTACLES:

RWY 35: 1077 FT MSL TOWER 335923.22N/0962345.47W.

REMARKS:

100 FT VEGETATION HEIGHT USED.

ORDER 8260.3G, ICA USED FOR DESIGN AND EVALUATION.

FLIGHT INSPECTED BY
BRYAN S VEIT

OFFICE
AJF

DATE
06/09/2026

Digitally signed by
TARA N MARTINELLI
Jun 10, 2026

DEVELOPED BY
CHARLES HIRST

Digitally signed by
CHARLES HIRST
Mar 19, 2026

OFFICE
AJV-A431

DATE
11/25/2025

APPROVED BY
CASIMIR L. TABAKA

OFFICE
AJV-A431

DATE
06/04/2026

TITLE
MANAGER

REQUIRED EFFECTIVE DATE:

ROUTINE

Digitally signed by
TARA N MARTINELLI
Jun 10, 2026

COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒

OTHER: ZFW, AMGR

CHANGES - REASONS:

1. TAKEOFF MINIMUMS CHANGED FROM "RWY 17, 35: STANDARD" TO "RWY 17: STANDARD. RWY 35: 400-3 OR STANDARD WITH MINIMUM CLIMB OF 205 FT/NM TO 1200 OR STANDARD AND CROSSING DER 8 FT ABOVE DER ELEV CLEARS TAKEOFF MINIMUMS OBSTACLES" – IAW 8260.46K APPENDIX D SECTION 1 PARA 2.E NEW CONTROLLING OBSTACLE
2. UPDATED TAKEOFF OBSTACLE NOTES – IAW 8260.46K APPENDIX D SECTION 2 PARA 2.H NEW SURVEY AND EVALUATION
3. CONTROLLING OBSTACLES ADDED "RWY 35: 1077 FT MSL TOWER 335923.22N/0962345.47W" – IAW 8260.46K APPENDIX D SECTION 1 PARA 2.I
4. REMARKS: ADDED 100 FT VEGETATION HEIGHT USED, AND ORDER 8260.3G, ICA USED FOR DESIGN AND EVALUATION - IAW 8260.46K 2-1-1.I AND FOR FUTURE SPECIALIST INFO.

QUALITY
42
CHECKED