

[Print](#)

Project Name: UVA

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-21 17:43:58.919376

Status: Verified

!FDC 6/5623 UVA IAP GARNER FLD, UVALDE, TX. RNAV (GPS) RWY 33, ORIG-B... LNAV CAT C VISIBILITY 1 3/8. DELETE GLS AND LNAV/VNAV MINIMUMS. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HDO ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHART VDP AT 1.31 NM RW33. CHART NOTE: VDP NA WHEN HDO USING ALTIMETER SETTING. DELETE RADAR REQUIRED PLANVIEW NOTE. CHANGE ALTERNATE MINIMUMS TO READ: STANDARD – CAT D 800- 2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 33, ORIG-C. 2604211743-PERM

Digitally signed by

CASEY D HILL

May 01, 2026

