

Print

Project Name: SNL RNAV (GPS) RWY 17

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-17 12:55:02.247348

Status: Verified

!FDC 6/4919 SNL IAP SHAWNEE RGNL, SHAWNEE, OK. RNAV (GPS) RWY 17, AMDT 1A... LNAV CAT C VISIBILITY 1. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT OWN0J TO READ: OWN0J/1.70 NM TO RW17 1660. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SRE ALTIMETER SETTING: INCREASE LPV DA TO 1313 FEET; INCREASE LNAV/VNAV DA TO 1487 FEET; INCREASE ALL MDAS 40 FEET AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING SRE ALTIMETER SETTING. CHANGE FOR UNCOMPENSATE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 SM AND LNAV CAT C TO 1 3/8 SM. THIS IS RNAV (GPS) RWY 17, AMDT 1B. 2604171255-PERM

Digitally signed by
CASEY D HILL
Apr 24, 2026

