

Print

Project Name: KLCK NEW CIRCLING RADII APPLIED

Project Reason: New circling areas evaluated. Backup altimeter notes and alternate minimums updated based on new circling HAA/visibilities only, other values not verified. Controlling obstacles: Cat A/B: Elevator (39-100864) 394650.00N/0825648.00W 876 (4D) + AC 50 + ROC 300 = MDA 1240. Cat C: TOWER (39-103369) 394946.54N/0825133.64W 929 (4D) + AC 50 + ROC 300 = MDA 1280. Cat D: AAO 394741.33N/0825023.71W 1100 (2C) + ROC 300 = MDA 1400. Radii: Cat A: 1.30 Cat B: 1.83 Cat C: 2.88 Cat D: 3.76. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-04-29 11:44:33.904293

1/9906

Status: Draft

IFDC X/XXXX LCK IAP RICKENBACKER INTL, COLUMBUS, OH. RNAV (GPS) RWY 23R, ORIG-C... CIRCLING CATS A/B MDA 1240/HAA 496, CAT C MDA 1280/HAA 536, CAT D MDA 1400/HAA 656. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JOHN GLENN COLUMBUS INTL ALTIMETER SETTING: INCREASE LPV DA TO 978 FEET; INCREASE LNAV/VNAV DA TO 1041 FEET AND ALL VISIBILITIES TO 1 SM; INCREASE ALL MDAS 40 FEET AND CIRCLING CAT D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 23R, ORIG-D. 2104291144-PERM

Digitally signed by  
**DAVID TEFFETELLER**  
May 04, 2021

