

Print

Project Name: GNF

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-18 13:16:47.087033

Status: Verified

!FDC 6/1147 GNF IAP GRENADA MUNI, GRENADA, MS. RNAV (GPS) RWY 31, AMDT 1C... LNAV CATS C/D VISIBILITY 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH - GPS. DELETE \*LNAV ONLY. CHANGE MIN ALT AT HUPIR TO READ: HUPIR/2.50 NM TO RW31 1080. CHANGE CHART VDP TO READ: CHART VDP AT 1.46 NM TO RW31. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GWO ALTIMETER SETTING: INCREASE LPV DA TO 577 FEET; INCREASE LNAV/VNAV DA TO 743 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CATS C/D 3/8 SM AND CIRCLING VISIBILITY ALL CATS 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING GWO ALTIMETER SETTING. DELETE PROFILE VGSI AND RNAV GLIDEPATH NOT COINCIDENT NOTE. THIS IS RNAV (GPS) RWY 31, AMDT 1D. 2603181316-PERM

Digitally signed by  
**CASEY D HILL**  
Mar 19, 2026

