

Print

Project Name: TME

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-20 20:16:02.544968

Status: Verified

!FDC 6/4927 TME IAP HOUSTON EXEC, HOUSTON, TX. RNAV (GPS) RWY 36, AMDT 1B... LNAV CAT C VISIBILITY 1 3/8. DELETE \*LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.31 NM TO RW36. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DWH ALTIMETER SETTING: INCREASE LPV DA TO 471 FEET; INCREASE LNAV/VNAV DA TO 719 FEET; INCREASE ALL MDAS 60 FEET AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING DWH ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 36, AMDT 1C. 2604202016-PERM

Digitally signed by  
**CASEY D HILL**  
Apr 24, 2026

