

Print

Project Name: GNV RNAV (GPS) RWY 11

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-18 14:51:08.368986

Status: Verified

IFDC 6/1149 GNV IAP GAINESVILLE RGNL, GAINESVILLE, FL. RNAV (GPS) RWY 11, AMDT 1C... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.25 NM TO RW11. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OCF ALTIMETER SETTING: INCREASE LPV DA TO 541 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 681 FEET; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/2 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING OCF ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NOTE TO READ: RWY 11 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 11, AMDT 1D. 2603181451-PERM

Digitally signed by
CASEY D HILL
Mar 19, 2026

