

Print

Project Name: MNN

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-07 19:42:18.823739

Status: Verified

!FDC 6/9775 MNN IAP MARION MUNI, MARION, OH. RNAV (GPS) RWY 7, ORIG-A... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT ZULGA TO READ: ZULGA/2.50 NM TO RW07 1820. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OSU ALTIMETER SETTING: INCREASE LPV DA TO 1327 FEET; INCREASE LNAV/VNAV DA TO 1466 FEET; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING OSU ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 7, ORIG-B. 2604071942-PERM

Digitally signed by
CASEY D HILL
Apr 10, 2026

