

Print

Project Name: M37

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-05-01 15:39:26.185754

Status: Active

!FDC 6/7325 M37 IAP RULEVILLE-DREW, DREW, MS. RNAV (GPS) RWY 18, ORIG... LNAV CAT C VISIBILITY 1 5/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: USE RNV ALTIMETER SETTING; WHEN NOT RECEIVED, USE GWO ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHART RNV AWOS-3. CHANGE HELICOPTER VISIBILITY REDUCTION NOTE TO READ: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 18, ORIG-A. 2605011539-PERM

Digitally signed by

CASEY D HILL

May 15, 2026

