

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>	<u>AMDT NO</u>	<u>ACTUAL EFFECTIVE DATE</u>
MCN	MACON	GA	4	

TAKEOFF MINIMUMS:

RWY 14, 32: STANDARD.

RWY 5: STANDARD WITH MINIMUM CLIMB OF 215 FT/NM TO 1500, OR 1000-3 FOR VCOA.

RWY 23: 300-1 7/8 OR STANDARD WITH MINIMUM CLIMB OF 230 FT/NM TO 700 OR STANDARD AND CROSSING DER 32 FT ABOVE DER ELEV
CLEARS TAKEOFF MINIMUMS OBSTACLES. ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB
GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 2100 FEET PRIOR TO DER.

TEXTUAL DEPARTURE PROCEDURES:

VISUAL CLIMB OVER AIRPORT:

RWY 5: OBTAIN ATC APPROVAL FOR VCOA WHEN REQUESTING IFR CLEARANCE. CLIMB IN VISUAL CONDITIONS TO CROSS MIDDLE GEORGIA
RGNL AIRPORT AT OR ABOVE 1200 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

RWY 5 LOW, CLOSE-IN OBSTACLES: OBSTACLES 35 FT AND BELOW. CROSSING DER 23 FT ABOVE DER ELEV CLEARS LOW, CLOSE-IN
OBSTACLES.

RWY 14, 32 LOW, CLOSE-IN OBSTACLES: OBSTACLES 35 FT AND BELOW. CROSSING DER 26 FT ABOVE DER ELEV CLEARS LOW, CLOSE-IN
OBSTACLES.

RWY 23 LOW, CLOSE-IN OBSTACLES: OBSTACLES 35 FT AND BELOW. CROSSING DER 27 FT ABOVE DER ELEV CLEARS LOW, CLOSE-IN
OBSTACLES.

RWY 23, TAKEOFF MINIMUMS OBSTACLES: TREES 1.2 NM FROM DER EXTENDING TO 1.6 NM FROM DER, LEFT OF CENTERLINE, UP TO 572 FT
MSL, 246 FT ABOVE DER. CROSSING DER 32 FT ABOVE DER ELEV CLEARS TAKEOFF MINIMUMS OBSTACLES.

CONTROLLING OBSTACLES:

RWY 5: 1199 FT MSL TOWER 324458.43N/0833334.45W (CLIMB GRADIENT) (CLIMB GRADIENT TERMINATION ALTITUDE).

RWY 23: 572 FT MSL TREE 324001.99N/0834050.44W (CLIMB GRADIENT) (CLIMB GRADIENT TERMINATION ALTITUDE) (CEILING) (DER CROSSING
HEIGHT), 567 FT MSL TREE 323959.74N/0834101.64W (VISIBILITY).

VISUAL CLIMB AREA OBSTACLE: 783 FT MSL TOWER 324214.16N/0834303.64W.

OBSTACLE OUTSIDE VISUAL CLIMB AREA MANDATING VCOA CLIMB TO ALTITUDE: 1199 FT MSL TOWER 324458.43N/0833334.45W.

REMARKS:

100 FT VEGETATION HEIGHT USED PER FPT.

ORDER 8260.3G, ICA USED FOR DESIGN AND EVALUATION.

FLIGHT INSPECTED BY *Digitally signed by*
ADAM K STALVEY **CASEY D HILL**

Aug 26, 2026

OFFICE
AJF **DATE**
08/24/2026

DEVELOPED BY *Digitally signed by*
CASIMIR L. TABAKA (THERON CYRUS) **CASEY D HILL**

Aug 26, 2026

OFFICE
AJV-A432 **DATE**
03/30/2026

APPROVED BY *Digitally signed by*
CASIMIR L. TABAKA **CASEY D HILL**

Aug 26, 2026

OFFICE
AJV-A432 **DATE**
09/24/2026 **TITLE**
MANAGER

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒

OTHER: ZTL, ATL APP CON, MCN TWR, MCN APT MGR

CHANGES - REASONS:

1. RWY 5: CHANGED TAKEOFF MINIMUMS FROM: "STANDARD WITH MINIMUM CLIMB OF 210 FEET PER NM TO 1500 OR 1000-2 1/2 FOR CLIMB IN
VISUAL CONDITIONS." TO: "STANDARD WITH MINIMUM CLIMB OF 215 FT/NM TO 1500 OR 1000-3 FOR CLIMB IN VISUAL CONDITIONS." - NEW
OBSTACLE EVALUATION/NEW ICA CRITERIA/8260.46K.

2. RWY 23: CHANGED TAKEOFF MINIMUMS FROM: "300-2 OR STANDARD WITH MINIMUM CLIMB OF 211 FT PER NM TO 700 OR ALTERNATIVELY,
WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1500 FEET PRIOR
TO DER" TO: "RWY 23: 300-1 7/8 OR STANDARD WITH MINIMUM CLIMB OF 230 FT/NM TO 700 OR STANDARD AND CROSSING DER 32 FT ABOVE
DER ELEV CLEARS TAKEOFF MINIMUMS OBSTACLES. ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB
GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 2100 FEET PRIOR TO DER." - NEW OBSTACLE EVALUATION/NEW ICA CRITERIA/8260.46K.

3. UPDATED TAKEOFF OBSTACLE NOTES (ALL RWYS) - NEW OBSTACLE EVALUATION.

QUALITY
42
CHECKED

AIRPORT ID
MCN

CITY
MACON

STATE
GA

AMDT NO
4

ACTUAL EFFECTIVE DATE

4. REMARKS: ADDED 100 FT VEGETATION HEIGHT USED PER FPT, AND ORDER 8260.3G, ICA USED FOR DESIGN AND EVALUATION - FOR FUTURE SPECIALIST INFO AND IAW 8260.46K 2-1-1.I.

QUALITY
42
CHECKED