

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
LEEAH	SIX	LEEAH6.LEEAH	FIVE	10/12/2017	
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWYS 28, 32: TURN RIGHT HEADING 045 AND OOD R-154 TO LEEAH INT, THENCE...

TAKEOFF RWYS 10, 14: TURN LEFT HEADING 109 AND OOD R-154 TO LEEAH INT, THENCE...

...THEN ON TRANSITION. MAINTAIN 1800, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
SMYRNA	LEEAH6.ENO	LEEAH INT	ENO VORTAC	275.00 (ENO R-095)	26.29	1800	1500	CROSS LEEAH AT/ ABOVE 1800
WATERLOO	LEEAH6.ATR	LEEAH INT	ATR VOR/DME	212.98 (ATR R-033)	29.61	1800	1500	CROSS LEEAH AT/ ABOVE 1800
COYLE	LEEAH6.CYN	LEEAH INT	CYN VORTAC	046.13 (CYN R-226)	41.21	1800	1600	CROSS LEEAH AT/ ABOVE 1800

PBN REQUIREMENT NOTES:

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 10, 14, 28, 32: STANDARD.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

MSA:

MSA FROM VCN VOR/DME 2100

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: TOP ALTITUDE: 1800

AIRPORT MV: MIV 11W/1985

QUALITY
12
CHECKED

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
LEEAH	SIX	LEEAH6.LEEAH	FIVE	10/12/2017	

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
KMIV	MILLVILLE	NJ

COMMUNICATIONS:

CHART: MILLVILLE CTAF, ASOS, ACY APP CON

FIXES AND/OR NAVAIDS:

VCN VOR/DME, RBV VORTAC, DQO VORTAC, ACY VORTAC.

REMARKS:

ABBREVIATED AMENDMENT.

100 FT VEGETATION USED PER FPT.

DO NOT CHART MOCA: FROM LEEAH INT TO ENO VORTAC, LEEAH INT TO CYN VORTAC, LEEAH INT TO ATR VOR/DME.

FLIGHT INSPECTED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17)
MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL
CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

SIGNATURE

Digitally signed by

CASIMIR L TABAKA

Apr 08, 2025

OFFICE

DATE

DEVELOPED BY

ROBERT HAMILTON (ANDRE TUCKER)

SIGNATURE

Digitally signed by

CASIMIR L TABAKA

Apr 08, 2025

OFFICE

AJV-A431

DATE

03/24/2025

APPROVED BY

ROBERT HAMILTON

SIGNATURE

Digitally signed by

CASIMIR L TABAKA

Apr 08, 2025

OFFICE

AJV-A433

DATE

08/07/2025

TITLE

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:** ZDC, ACY/DOV, ATCT/APPCON, APT AMGR

CHANGES - REASONS:

1. FIXES AND/OR NAVAIDS: REMOVED SBY VORTAC. - SBY DECOM.

2. ADDITIONAL FLIGHT DATA: ADDED KMIV MAGVAR. - IAW 8260.46J.

3. MSA: ADDED VCN VORTAC MSA. - IAW 8260.46J.

4. REMARKS: ADDED ABBREVIATED AMENDMENT AND 100 FT VEGETATION USED PER FPT. - IAW 8260.46J.

5. REMARKS: ADDED DO NOT CHART MOCA: FROM LEEAH INT TO ENO VORTAC, LEEAH INT TO CYN VORTAC, LEEAH INT TO ATR VORTAC. - IAW AFS CLARIFICATION DP MOCA MEMO.

5/22/23: THIS IS AN CORRECTED COPY OF THE FORM APPROVED ON 4/8/25.

1. WATERLOO TRANSISTIONS: ATR VORTAC CHANGED TO ATR VOR/DME

2. REMARKS: DO NOT CHART MOCA "LEEAH INT TO ATR VORTAC" CHANGED TO "LEEAH INT TO ATR VOR/DME".

QUALITY
12
CHECKED