

WAAS CH 97517 W35A	APP CRS 355°	Rwy Idg 7198 TDZE 1776 APT Elev 1791
--------------------------	------------------------	---

RNAV (GPS) RWY 35R

ABILENE RGNL (KABI)

RNP APCH - GPS.	MISSED APPROACH: CLIMB TO 4000 DIRECT GOFDO AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000.
FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -11°C OR ABOVE 53°C. BARO-VNAV AND VDP NA WHEN USING DYS ALTIMETER SETTING. WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DYS ALTIMETER SETTING AND INCREASE LPV DA TO 1997 FEET; INCREASE LNAV/VNAV DA TO 2210 FEET; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C/D/E TO RVR 5500 AND CIRCLING VISIBILITY CAT D 1/4 SM. FOR INOPERATIVE ALS, INCREASE LPV CAT E VISIBILITY TO RVR 4000, LNAV/VNAV ALL CATS TO RVR 6000, AND LNAV CATS C/D/E TO 1 3/8 SM. *RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.	

ATIS 118.25	ABILENE APP CON 125.0 338.3 (EAST) 127.2 282.3 (WEST)	ABILENE TOWER 120.1 257.8	GND CON 121.7 348.6
-----------------------	---	-------------------------------------	-------------------------------

