

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
PORTLAND	SEVEN	PWM7.PWM	SIX	05/21/2020	

TYPE:

<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
☐	☐	☒	☐	☐

DP ROUTE DESCRIPTION:

TAKEOFF RWY 11: CLIMB ON HEADING 110.30 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE.
TAKEOFF RWY 18: CLIMB ON HEADING 178.22 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE.
TAKEOFF RWY 29: CLIMB ON HEADING 290.32 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE.
TAKEOFF RWY 36: CLIMB ON HEADING 358.21 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	---------------------------------	------------------------	----------------------	---------------	-----------------	------------	-------------	--------------------------------

PBN REQUIREMENT NOTES:

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED.

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 18, 29: STANDARD.
RWY 11: STANDARD WITH MINIMUM CLIMB OF 280 FT/NM TO 400.
RWY 36: STANDARD WITH MINIMUM CLIMB OF 240 FT/NM TO 600.

TAKEOFF OBSTACLE NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 11: 248 FT MSL TREE 433850.16N/0701632.42W.
RWY 36: 429 FT MSL TOWER 434123.60N/0701859.83W.

MSA:

ENE VOR/DME 055 CW 235, 1900; 235 CW 325, 3100; 325 CW 055, 3600

LOST COMMUNICATION PROCEDURES:

ADDITIONAL FLIGHT DATA:

AIRPORT MV: PWM 15W/2020.
DME/DME ASSESSMENT: SAT (RNP 2.0).
CHART: TOP ALTITUDE: ASSIGNED BY ATC.

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
PWM	PORTLAND	ME

COMMUNICATIONS:

CHART: ATIS, CLNC DEL, GND CNTL, TOWER

QUALITY
42
CHECKED

FIXES AND/OR NAVAIDS:

AUG VOR/DME
BGR VORTAC
CON VOR/DME
MPV VOR/DME
CAM VOR/DME
BTV VOR/DME
BOS VOR/DME
LFV VOR/DME

REMARKS:

ORDER 8260.3G, LEGACY ICA USED FOR DESIGN AND EVALUATION.
VEGETATION HEIGHT OF 100 FT USED PER FPT CHECKLIST.
WAIVERS (2): LESS THAN STANDARD ROC; AN ATC REQUESTED MAINTAINED ALTITUDE LOWER THAN THE UNRESTRICTED CLIMB ALLOWED BY TERPS EVALUATION.

FLIGHT INSPECTED BY

OFFICE

DATE

DEVELOPED BY

RAKE MCGRAW (JUDITH TUTTLE)

OFFICE

AJV-A431

DATE

01/06/2026

APPROVED BY

RAKE MCGRAW

OFFICE

AJV-A422

DATE

06/04/2026

TITLE

MANAGER

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒

OTHER: ZBW, PWM APP CON, PWM ATCT, AMGR

CHANGES - REASONS:

1. DP ROUTE DESCRIPTION: UPDATED FROM "TAKEOFF RWYS 11, 18, 29, 36: FLY RUNWAY HEADING OR AS ASSIGNED BY ATC; FOR RADAR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN 3000 OR AS ASSIGNED BY ATC. EXPECT CLEARANCE TO FILED ALTITUDE FIVE (5) MINUTES AFTER DEPARTURE. WHEN TOWER CLOSED MAINTAIN 5000, CONTACT BOSTON CENTER" TO "TAKEOFF RWY 11: CLIMB ON HEADING 110.30 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE," "TAKEOFF RWY 18: CLIMB ON HEADING 178.22 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE," "TAKEOFF RWY 29: CLIMB ON HEADING 290.32 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE" AND "TAKEOFF RWY 36: CLIMB ON HEADING 358.21 FOR VECTORS TO ASSIGNED ROUTE/NAVAID/FIX. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 5 MINUTES AFTER DEPARTURE" – IAW 8260.46K.
2. EQUIPMENT REQUIREMENT NOTES: ADDED "RADAR REQUIRED" – IAW 8260.46K.
3. TAKEOFF MINIMUMS: UPDATED RWY 11: FROM "300-1 1/4 OR STANDARD WITH MINIMUM CLIMB OF 272 FT PER NM TO 400" TO "STANDARD WITH MINIMUM CLIMB OF 280 FT/NM TO 400" – OBSTACLE CLIMB GRADIENT USED TO MATCH ODP.
4. TAKEOFF MINIMUMS: UPDATED RWY 36 FROM "400-2 3/4 OR STANDARD WITH MINIMUM CLIMB OF 235 FT PER NM TO 600" TO "STANDARD WITH MINIMUM CLIMB OF 240 FT/NM TO 600" – OBSTACLE CLIMB GRADIENT USED TO MATCH ODP.
5. CONTROLLING OBSTACLES: UPDATED RWY 11 FROM "251 FT MSL TREE" TO "248 FT MSL TREE 433850.16N/0701632.42W" – UPDATED SURVEY, NEW OBSTACLE IDENTIFIED, IAW 8260.46K.
6. CONTROLLING OBSTACLES: UPDATED RWY 36 FROM "429 FT MSL TOWER 434123.60N/0701859.83W. 432 FT MSL TOWER 434126.41N/0701903.01W" TO "429 FT MSL TOWER 434123.60N/0701859.83W" – UPDATED SURVEY, NEW OBSTACLE IDENTIFIED, IAW 8260.46K.
7. MSA: ADDED ENE VOR/DME 055 CW 235, 1900; 235 CW 325, 3100; 325 CW 055, 3600 – MATCHED CONVENTIONAL IAPS AT KPWM, IAW 8260.46K.
8. ADDITIONAL FLIGHT DATA: UPDATED NOTE FROM "REFERENCE MAG VAR: KPWM 15W EPOCH YR: 2020" TO "AIRPORT MV: PWM 15W/2020" – IAW 8260.46K.
9. ADDITIONAL FLIGHT DATA: ADDED "DME/DME ASSESSMENT: SAT (RNP 2.0)." – IAW 8260.46K.
10. COMMUNICATIONS: UPDATED FROM "ATIS, CLNC DEL, GND CNTL, TOWER, PWM DEP CON, ZBW" TO "ATIS, CLNC DEL, GND CNTL, TOWER, PWM DEP CON" – REMOVED ZBW PER ATC REQUEST, UPDATED IAW 8260.46K.
11. FIXES AND/OR NAVAIDS: REMOVED "SYR VORTAC" – DUE TO EXCESSIVE DISTANCE FROM AIRPORT.

12. REMARKS: ADDED "VEGETATION HEIGHT OF 100 FT USED PER FPT CHECKLIST." "ORDER 8260.3G, LEGACY ICA USED FOR DESIGN AND EVALUATION" AND "WAIVERS (2): LESS THAN



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
PORTLAND	SEVEN	PWM7.PWM	SIX	05/21/2020	

STANDARD ROC; AN ATC REQUESTED MAINTAINED ALTITUDE LOWER THAN THE UNRESTRICTED CLIMB ALLOWED BY TERPS EVALUATION" – FOR FUTURE SPECIALISTS' INFORMATION, IAW 8260.46K.

