

Print

Project Name: GGI

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-17 17:54:51.847587

Status: Verified

!FDC 6/9950 GGI IAP GRINNELL RGNL, GRINNELL, IA. RNAV (GPS) RWY 13, AMDT 1... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TNU ALTIMETER SETTING: INCREASE LPV DA TO 1324 FEET; INCREASE LNAV/VNAV DA TO 1455 FEET; INCREASE ALL MDAS 40 FEET. CHANGE BARO-VNAV NA WHEN USING NOTE TO READ: BARO-VNAV NA WHEN USING TNU ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NOTE TO READ: RWY 13 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 13, AMDT 1A. 2603171754-PERM

Digitally signed by
CASEY D HILL
Mar 18, 2026

