

Print

Project Name: MCK ILS OR LOC/DME RWY 12

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-01 13:23:58.974152

Status: Verified

!FDC 6/9739 MCK IAP MC COOK BEN NELSON RGNL, MC COOK, NE. ILS OR LOC/DME RWY 12, ORIG-B... S-LOC 12 CAT C VISIBILITY 1 1/4. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE IML ALTIMETER SETTING: INCREASE S-ILS 12 DA TO 2997 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 220 FEET AND S-LOC 12 VISIBILITY CAT B 1/4 SM, S-LOC VISIBILITY CAT C 5/8 SM, AND CIRCLING VISIBILITY CATS A/B/C 3/4 SM. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING IML ALTIMETER SETTING. DELETE FOR INOPERATIVE MALSR, WHEN USING IMPERIAL MUNI ALTIMETER SETTING NOTE. THIS IS ILS OR LOC/DME RWY 12, ORIG-C. 2604011323-PERM

Digitally signed by  
**CASEY D HILL**  
Apr 10, 2026

