

[Print](#)

Project Name: NEW

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-08 18:52:49.606066

Status: Verified

IFDC 6/2208 NEW IAP LAKEFRONT, NEW ORLEANS, LA. RNAV (GPS) RWY 18R, AMDT 2A... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.82 NM TO RW18R. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, LNAV CATS A/B TO 1 SM, AND LNAV CATS C/D TO 1 3/4 SM. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MSY ALTIMETER SETTING: INCREASE LPV DA TO 291 FEET; INCREASE LNAV/VNAV DA TO 554 FEET; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C 1/8 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING MSY ALTIMETER SETTING. CHANGE FOR UNCOMPENSATE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NA NOTE TO READ: RWY 18R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE FOR INOPERATIVE MALSR WHEN USING LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING NOTE. DELETE RADAR REQUIRED PLANVIEW NOTE. THIS IS RNAV (GPS) RWY 18R, AMDT 2B. 2604081852-PERM

Digitally signed by
CASEY D HILL
Apr 14, 2026

