

Print

Project Name: LNC

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-30 20:11:36.663631

Status: Verified

!FDC 6/9735 LNC IAP LANCASTER RGNL, LANCASTER, TX. RNAV (GPS) RWY 31, AMDT 1A... LNAV CAT C VISIBILITY 1 1/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT OTAZY TO READ: OTAZY/1.50 NM TO RW31 1000. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RBD ALTIMETER SETTING: INCREASE LPV DA TO 732 FEET; INCREASE LNAV/VNAV DA TO 970 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING RBD ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. DELETE PLANVIEW NOTE RADAR REQUIRED. THIS IS RNAV (GPS) RWY 31, AMDT 1B. 2603302011-PERM

Digitally signed by
CASEY D HILL
Apr 10, 2026

