

Print

Project Name: FOD

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-13 12:40:37.42795

Status: Verified

!FDC 6/9140 FOD IAP FORT DODGE RGNL, FORT DODGE, IA. RNAV (GPS) RWY 6, AMDT 1B... LNAV CAT C VISIBILITY 5/8. CHANGE PBN REQUIREMENTS NOTE TO: RNP APCH-GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.14 NM TO RW06. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 1/8 SM AND LNAV CAT D VISIBILITY TO 1 1/8 SM. DELETE NOTE FOR INOPERATIVE MALSR WHEN USING WEBSTER CITY ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 MILE. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EBS ALTIMETER SETTING: INCREASE LPV DA TO 1349 FEET; INCREASE LNAV/VNAV DA TO 1567 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/4 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING EBS ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 6, AMDT 1C. 2603131240-PERM

Digitally signed by
CASEY D HILL
Mar 17, 2026

