

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
AHABB (OBSTACLE)	ONE	AHABB1.AHABB	NONE		

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

**DP ROUTE DESCRIPTION:**

TAKEOFF RWY 10L: CLIMB ON HEADING 098.78 TO INTERCEPT COURSE 019.83 TO AHABB.

**TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):**

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	---------------------------------	------------------------	----------------------	---------------	-----------------	------------	-------------	--------------------------------

**PBN REQUIREMENT NOTES:**

RNAV 1 - GPS

**EQUIPMENT REQUIREMENT NOTES:**

**PROCEDURAL DATA NOTES:**

**TAKEOFF MINIMUMS:**

RWY 10L: STANDARD WITH MINIMUM CLIMB OF 505 FT/NM TO 520.

**TAKEOFF OBSTACLES NOTES:**

RWY 10L: LIGHTING 9 FT FROM DER, 54 FT RIGHT OF CENTERLINE, 2 FT AGL/17 FT MSL.

LIGHTING 9 FT FROM DER, 55 FT LEFT OF CENTERLINE, 2 FT AGL/17 FT MSL.

POLE 1466 FT FROM DER, 843 FT RIGHT OF CENTERLINE, 53 FT AGL/64 FT MSL.

**CONTROLLING OBSTACLES:**

**MSA:**

PBI, 2600

**LOST COMMUNICATIONS PROCEDURES:**

**ADDITIONAL FLIGHT DATA:**

DME/DME ASSESMENT: NOT CONDUCTED

AIRPORT MV: PBI 6W/2010

**AIRPORTS SERVED:**

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>	<u>QUALITY</u>
PBI	WEST PALM BEACH	FL	8

QUALITY  
8  
CHECKED

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
AHABB (OBSTACLE)	ONE	AHABB1.AHABB	NONE		

**COMMUNICATIONS:**

CHART: CLNC DEL, ATIS, CPDLC, GND CON

**FIXES AND/OR NAVAIDS:**

**REMARKS:**

505 FT/NM CG REQUIRED FOR EARLY TURN PROCEDURE DESIGN TO REMAIN CLEAR OF PROHIBITED AREA CENTERED ON 0.5NM AROUND 264037.00N/0800216.00W.  
 APPROVAL LETTER ON FILE FOR CG GREATER THAN 500 FT/NM.  
 75' VEGETATION HEIGHT USED ON OTHER PROCEDURES PER FPT

**FLIGHT INSPECTED BY**

MATTHEW OLSTAD

**SIGNATURE**

*Digitally signed by*  
**CASIMIR L TABAKA**  
 Dec 01, 2025

**OFFICE**

FICO

**DATE**

11/20/2025

**DEVELOPED BY**

LEO PALMER

**SIGNATURE**

*Digitally signed by*  
**CASIMIR L TABAKA**  
 Dec 01, 2025

**OFFICE**

AJV-A432

**DATE**

10/10/2025

**APPROVED BY**

CASIMIR TABAKA

**SIGNATURE**

*Digitally signed by*  
**CASIMIR L TABAKA**  
 Dec 01, 2025

**OFFICE**

AJV-A432

**DATE**

12/18/2025

**TITLE**

MANAGER

**REQUIRED EFFECTIVE DATE**

ROUTINE

**COORDINATED WITH:**

**A4A**  **ALPA**  **AOPA**  **APA**  **HAI**  **NBAA**  **OTHER:**ZMA ARTCC, PBI DEP CON, PBI ATCT, AMGR

**CHANGES - REASONS:**

ORIGINAL - REPLACED RWY 10L TEXTUAL DEPARTURE PROCEDURE.



**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
AHABB (OBSTACLE)	ONE	AHABB1.AHABB	NONE		

  

<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW10L (AER)*	264058.97N/0800616.92W	N							*DISPL THLD (1200 FT)
	264051.81N/0800333.11W			VI	092.78	2.45			CG 505 FT PER NM TO 520
AHABB	264832.70N/0800126.85W	Y	FB	CF	013.83	7.89			

