

Print

Project Name: KUES RNAV GPS RWY 10 - NEW CIRCLING RADII

Project Reason: Project Reason: New circling areas established. Controlling obstacles: Cat A: TOWER (55-079156) 430158.43N/0881225.42W, 1132, 2C (new, maintained previous minimums). 1132 + 300 (ROC) = 1440. Cat B: TANK (55-001613) 430214.68N/0881710.79W, 1195, 1A (new). 1195 + 300 (ROC) = 1500. Cat C: TOWER (55-000809) 430129.88N/0881123.79W, 1238, 2C (new). 1238 + 300 (ROC) = 1540. Cat D: AAO 430141.35N/0882002.33W, 1340, 2C (new). 1340 + 300 (ROC) = 1640. Radii: Cat A: 1.30, Cat B: 1.84, Cat C: 2.89, Cat D: 3.78. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: Kweku Donkor

Last Updated At: 2021-04-30 11:52:50.070809

1/8322

Status: Verified

!FDC X/XXXX UES IAP WAUKESHA COUNTY, WAUKESHA, WI. RNAV (GPS) RWY 10, ORIG-A... CIRCLING CAT B MDA 1500/HAA 589, CAT C MDA 1540/HAA 629, CAT D MDA 1640/HAA 729. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LAWRENCE J TIMMERMAN ALTIMETER SETTING: INCREASE LPV DA TO 1147 FEET, LNAV/VNAV DA TO 1583 FEET AND ALL CATS VISIBILITY 1/4 SM; INCREASE ALL MDAS 60 FEET AND CIRCLING CAT C AND D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 10, ORIG-B. 2104301152-PERM



Digitally signed by
DAVID TEFFETELLER
May 11, 2021