


LOC/DME I-JFI 111.7 Chan 54	APP CRS 016°	Rwy Idg 7002 TDZE 2 Apt Elev 3
---	------------------------	---

ILS or LOC RWY 2
LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

DME required for procedure entry. Autopilot coupled approach NA below 880. Rwy 2 helicopter visibility reduction below RVR 4000 NA.		MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 on RQR VOR/DME R-082 to SNAKI INT/RQR 36.6 DME and hold.		
--	--	--	--	--

D-ATIS 127.55	NEW ORLEANS APP CON WEST 125.5 350.35 EAST 133.15 290.3	NEW ORLEANS TOWER 119.5 254.3	GND CON 121.9 273.525	CLNC DEL 120.925	CPDLC
-------------------------	---	---	---------------------------------	----------------------------	-------



VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 52).		1500	3000	SNAKI
ROYUL INT I-JFI 14		POVVI INT I-JFI 7.4	YERUB I-JFI 2.7	I-JFI 1.3
GS 3.00° TCH 56		2000	480	
6.6 NM		4.7 NM	1.4 NM	
CATEGORY	A	B	C	D
S-ILS 2	415/60		413 (500-1¼)	
S-LOC 2	480/55	478 (500-1)	480-1¾	478 (500-1¾)
CIRCLING	520-1 517 (600-1)	540-1 537 (600-1)	580-1½ 577 (600-½)	580-2 577 (600-2)
YERUB FIX MINIMUMS				
S-LOC 2	440/55	438 (500-1)	440-1¼	438 (500-1¼)
CIRCLING	520-1 517 (600-1)	540-1 537 (600-1)	580-1½ 577 (600-½)	580-2 577 (600-2)

