

Print

Project Name: GRR

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-18 19:04:39.528282

Status: Verified

!FDC 6/2588 GRR IAP GERALD R FORD INTL, GRAND RAPIDS, MI. RNAV (GPS) RWY 26L, AMDT 1C... LNAV/VNAV CATS A/B/C VISIBILITY RVR 2600. LNAV CAT C VISIBILITY RVR 5000. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.31 NM TO RW26L. CHANGE MIN ALT AT DAXEJ TO READ: DAXEJ/2.50 NM TO RW26L 1640. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. CHANGE FOR INOPERATIVE ALS NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV CAT D VISIBILITY TO RVR 5000 AND LNAV CATS C/D TO 1 3/8 SM. THIS IS RNAV (GPS) RWY 26L, AMDT 1D. 2603181904-PERM

Digitally signed by
CASEY D HILL
Mar 24, 2026

