

Print

Project Name: 51J

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-02-18 14:17:30.975065

Status: Verified

!FDC **6/6907** 51J IAP LAKE CITY MUNI CJ EVANS FLD, LAKE CITY, SC. RNAV (GPS) RWY 1, ORIG-A... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: USE CKI ALTIMETER SETTING; WHEN NOT RECEIVED, USE FLO ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET AND CIRCLING VISIBILITY CATS B/C 1/4 SM. CHANGE CHART KINGSTREE AWOS-3 TO CHART CKI AWOS-3. CHANGE CHART NOTE: STRAIGHT-IN MINIMUMS NA AT NIGHT TO CHART NOTE: PROCEDURE NA AT NIGHT. CHANGE CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA TO CHART NOTE: RWY 1 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 1, ORIG-B. 2602181417-PERM

Digitally signed by
CASEY D HILL
Feb 19, 2026

