

[Print](#)

Project Name: EET

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-09 13:42:15.004498

Status: Verified 6/8976

IFDC X/XXXX EET IAP SHELBY COUNTY, ALABASTER, AL. RNAV (GPS) RWY 16, AMDT 1A... LNAV CAT C VISIBILITY 1 7/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT WEDAS TO READ: WEDAS/2.30 NM TO RW16 1360. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BHM ALTIMETER SETTING: INCREASE LPV DA TO 993 FEET; INCREASE LNAV/VNAV DA TO 1238 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING BHM ALTIMETER SETTING. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NOTE TO READ: RWY 16 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 16, AMDT 1B. 2603091342-PERM

Digitally signed by

BEV L BORDY

Mar 17, 2026

