

[Print](#)

Project Name: MBG

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums. Add asterisk note to raise stepdown altitude to 2440' when using backup altimeter.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-31 17:43:43.077551

Status: Verified

!FDC 6/9773 MBG IAP MOBRIDGE MUNI, MOBRIDGE, SD. RNAV (GPS) RWY 12, ORIG-B... LNAV CAT C VISIBILITY 1 5/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PIR ALTIMETER SETTING AND INCREASE ALL MDAS 180 FEET AND LNAV VISIBILITY CAT C 3/8 SM, LNAV VISIBILITY CAT D 1/4 SM, AND CIRCLING VISIBILITY ALL CATS 3/4 SM. CHANGE MIN ALT AT PUCBI TO READ: PUCBI/2.10 NM TO RW12 2400*.

*2440 WHEN USING PIR ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 12, ORIG-C. 2603311743-PERM

Digitally signed by

CASEY D HILL

Apr 10, 2026

