

Print

Project Name: SNL RNAV (GPS) RWY 35

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-17 15:59:48.242592

Status: Verified

!FDC 6/4920 SNL IAP SHAWNEE RGNL, SHAWNEE, OK. RNAV (GPS) RWY 35, ORIG-C... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT IVICE TO READ: IVICE/2.10 NM TO RW35 1780. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SRE ALTIMETER SETTING: INCREASE LPV DA TO 1357 FEET; INCREASE LNAV/VNAV DA TO 1605 FEET; INCREASE ALL MDAS 40 FEET AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING SRE ALTIMETER SETTING. CHANGE FOR UNCOMPENSATE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. CHART VDP AT 1.29 NM TO RW35. CHART NOTE: RWY 35 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 35, ORIG-D. 2604171559-PERM

Digitally signed by
CASEY D HILL
Apr 24, 2026

