

Print

Project Name: DKB RNAV (GPS) RWY 27

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-05 12:59:27.838478

Status: Verified 6/8952

!FDC X/XXXX DKB IAP DE KALB TAYLOR MUNI, DE KALB, IL. RNAV (GPS) RWY 27, AMDT 1A... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.34 NM TO RW27. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARR ALTIMETER SETTING: INCREASE LPV DA TO 1223 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1378 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING ARR ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. GS ALT AT WAVBI 2500. THIS IS RNAV (GPS) RWY 27, AMDT 1B. 2603051259-PERM

Digitally signed by
BEV L BORDY
Mar 17, 2026

