

[Print](#)

Project Name: MCK RNAV (GPS) RWY 12

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-01 13:22:32.938032

Status: Verified

!FDC 6/9740 MCK IAP MC COOK BEN NELSON RGNL, MC COOK, NE. RNAV (GPS) RWY 12, AMDT 1B... LNAV CAT C VISIBILITY 1 1/4. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.75 NM TO RW12. DELETE FOR INOPERATIVE MALSR NOTE. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE IML ALTIMETER SETTING: INCREASE LPV DA TO 3054 FEET AND ALL VISIBILITIES 1/2 SM; INCREASE LNAV/VNAV DA TO 3454 FEET; INCREASE ALL MDAS 220 FEET AND LNAV VISIBILITY CAT B 1/4 SM, LNAV VISIBILITY CAT C 5/8 SM, AND CIRCLING VISIBILITY CATS A/B/C 3/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING IML ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 12, AMDT 1C. 2604011322-PERM

Digitally signed by

CASEY D HILL

Apr 10, 2026

