

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
DITTI	ONE	DITTI1.DITTI	NONE		
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 13: CLIMB ON HEADING 133.79 TO 4997, THEN CLIMBING RIGHT TURN DIRECT TO CROSS DITTI AT 9000, THENCE ...

TAKEOFF RWY 31: CLIMB ON HEADING 313.80 TO 4997, THEN CLIMBING LEFT TURN DIRECT TO CROSS DITTI AT 9000, THENCE ...

...THEN ON (TRANSITION). MAINTAIN 9000, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
WASATCH	DITTI1.TCH	DITTI	KOONA	TRACK 272.12	9.15	9900	8100	
		KOONA	TCH VORTAC	TRACK 355.93	41.02	11200	9100	
DAHLI	DITTI1.DAHLI	DITTI	NEPHI	TRACK 180.11	7.55	9900	7200	
		NEPHI	BOTSS	TRACK 151.02	7.87	9900	8200	
		BOTSS	DAHLI	TRACK 175.46	10.77	9900	9100	

PBN REQUIREMENT NOTES:

RNAV 1-GPS

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 13: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 4997, THEN 326 FT/NM TO 7600.

RWY 31: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 4997.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

CONTROLLING OBSTACLES:

RWY 13: 6837 MSL AAO 400545.00N/1114930.00W

MSA:

MSA FROM KPVU, 13200



LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:
DME/DME ASSESSMENT: UNSAT.
CHART: TOP ALTITUDE: 9000
AIRPORT MV: PVU 12E/2010

AIRPORTS SERVED:

AIRPORT ID	CITY	STATE
KPVU	PROVO	UT

COMMUNICATIONS:

CHART: ATIS, PVU ATCT, GND CON

FIXES AND/OR NAVAIDS:

REMARKS:
FIX DAHLI ALSO USED DAILY BY ZLC FOR OTHER LOCAL TASKS.
RWY 13/31 LNAV ENGAGEMENT CLIMB GRADIENT 500 FT/NM TO 4997.
PER FPT REQUEST 30 FT BOAT OBS AND 50 FT VEGETATION WERE INCLUDED INTO BUILD.

FLIGHT INSPECTED BY	Digitally signed by	SIGNATURE	OFFICE	DATE	
THOMAS E MOLOKIE	JOHN BORDY		FPO	08/21/2024	
	Aug 27, 2024				
DEVELOPED BY	Digitally signed by	SIGNATURE	OFFICE	DATE	
JOHN BORDY (TROY PURNELL)	JOHN BORDY		AJV-A44	05/01/2024	
	Aug 27, 2024				
APPROVED BY	Digitally signed by	SIGNATURE	OFFICE	DATE	TITLE
JOHN BORDY	JOHN BORDY		AJV-A33	08/27/2024	MANAGER
	Aug 27, 2024				

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A☒ ALPA☒ AOPA☒ APA☐ HAI☐ NBAA☒ OTHER:ZLC, SLC APP CON, UT AERO, AMGR, PVU ATCT.

CHANGES - REASONS:

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME				NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		ACTUAL EFFECTIVE DATE	
DITTI				ONE		DITT11.DITTI		NONE					
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS				
RW13 (AER)	401348.77N/1114356.80W	N	-	-	-	-							
4997 MSL	-	-	-	VA	145.79		AT/ABOVE 4997		CG 500 FT/NM TO 4997, THEN 326 FT/NM TO 7600				
DITTI	400808.34N/1115447.54W	Y	FB	DF	-	-	AT 9000		RIGHT TURN				
RW31 (AER)	401238.47N/1114254.47W	N	-	-	-	-							
4997 MSL	-	-	-	VA	325.80		AT/ABOVE 4997		CG 500 FT/NM TO 4997				
DITTI	400808.34N/1115447.54W	Y	FB	DF	-	-	AT 9000		LEFT TURN				
DITTI	400808.34N/1115447.54W	Y	-	IF	-	-			DITT11.TCH				
KOONA	401021.81N/1120622.18W	Y	FB	TF	284.12	9.15							
TCH VORTAC	405100.93N/1115854.86W	Y	FB	TF	007.93	41.02							
DITTI	400808.34N/1115447.54W	Y	-	IF	-	-			DITT11.DAHLI				
NEPHI	400045.29N/1115651.16W	Y	FB	TF	192.11	7.55							
BOTSS	395313.09N/1115351.97W	Y	FB	TF	163.02	7.87							
DAHLI	394231.76N/1115540.69W	Y	FB	TF	187.46	10.77							

