FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAI	<u>/IE</u>					NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
AURELI	A					FOUR	AUREL4.SIRPE	THREE	7/21/2016	
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV					
			\boxtimes		\boxtimes					

DP ROUTE DESCRIPTION:

TAKEOFF RWY 13: CLIMB DIRECT AMOME, THEN ON TRACK 152.25 TO SIRPE, CROSS SIRPE AT OR ABOVE 8400, THEN ON TRANSITION. MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	TRANSITION COMPUTER CODE	<u>FROM</u> FIX/NAVAID	<u>TO</u> FIX/NAVAID	COURSE	DISTANCE	<u>MEA</u>	MOCA	CROSSING ALTITUDE/FIXES
PRESN	AUREL4.PRESN	SIRPE	PRESN	TRACK 196.91	8.46	8600	8100	AT/ABOVE 8600
REAPS	AUREL4.REAPS	SIRPE	REAPS	TRACK 137.84	11.36	9500	8800	AT/ABOVE 9500
SOLDE	AUREL4.SOLDE	SIRPE	SOLDE	TRACK 241.59	16.18	9500	8200	

PBN REQUIREMENT NOTES:

RNAV 1 - GPS

EQUIPMENT REQUIREMENT NOTES:

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 31: NA - OBSTACLES.

RWY 13: STANDARD WITH A MINIMUM CLIMB OF 420 FT PER NM TO 6200.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 13: 5939 FT MSL TREE 432742.30N/1141652.86W.

MSA:

MSA FROM KSUN, 13200.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: UNSAT. AIRPORT MAG VAR: KSUN 13E/2020.

CHART: TOP ALTITUDE: ASSIGNED BY ATC.

CHART: V444-500 WEST OF SOLDE, V500 FROM EAST OF SOLDE TO EAST OF REAPS, V484 SOUTHWEST OF PRESN, V101 SOUTHEAST OF REAPS.

OUALITY 23 CHECKE

DD NAME	NUMBER	DD COMPUTED CODE	OUREROERER NUMBER	DATED	ACTUAL EFFECTIVE DATE
<u>DP NAME</u> AURELIA	<u>NUMBER</u> FOUR	DP COMPUTER CODE AUREL4.SIRPE	SUPERSEDED NUMBER THREE	<u>DATED</u> 7/21/2016	ACTUAL EFFECTIVE DATE
AIRPORTS SERVED:	1 0011	NONEL4.ONG E	THILL	772 1720 10	
AIRPORTS SERVED. AIRPORT ID		CITY			STATE
					
KSUN		HAILEY			ID
COMMUNICATIONS:					
CHART: ZLC ARTCC, TOWER, GROUND CONTROL, UNICOM.					
FIXES AND/OR NAVAIDS:					
REMARKS:					
		Digitally signed by			
FLIGHT INSPECTED BY SIGNATURE	-	CASIMIR L TABAKA	<u>OFFICE</u>	DATE	
PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-1000) MEMO, DA 2020, SUBJECT: FLIGHT INSPECTION OF NEW CONTROLLING OBSTACLE	,	Mar 06, 2025			
		lly signed by			
DEVELOPED BY SIGNATURE	CASIMI	R L TABAKA	<u>OFFICE</u>	DATE	
JOSEPH BLANCO	Mar	06, 2025	AJV-A432	01/15/2025	
APPROVED BY SIGNATURE	:		OFFICE	DATE	<u>TITLE</u>
	Digitally sig	ned by		DATE	
BEVERLY BORDY	CASIMIR L T	ABAKA	AJV-A430		MANAGER
REQUIRED EFFECTIVE DATE	Mar 06, 2	025			
ROUTINE					
COORDINATED WITH:					
A4A ALPA AOPA AOPA APA HAI NBAA	OTHER: ZLC	, SUN ATCT, AMGR			
CHANGES - REASONS:					
1. UPNUMBERED DEPARTURE FROM THREE TO FOUR - PROCEDURE (AB 2. ADDED MSA ENTRY - UPDATED CRITERIA PER ORDER 8260.46.	BREVIATED) AME	ENDMENT.			
3. REMOVED 10000 FT TOP ALTITUDE FOR PRESN AND REAPS TRANSITIO		EST.			
4. CHANGED ALL TRANSITIONS TO TOP ALITUDE: ASSIGNED BY ATC - ATO 5. ADDED MOCAS FOR ALL EN ROUTE TRANSITIONS - UPDATED CRITERIA		60.46			
6. CORRECTED 8260-15C DISPLITH DITO AMOME DISTANCE FROM 2.26 N					

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE DEPARTURE (DATA RECORD)

DP NAME						NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
AURELIA						FOUR	AUREL4.SIRPE	THREE	7/21/2016	
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	<u>SPEED</u>	REMARKS	
RW13 (AER)*	433030.34N/1141800.23W	N	-	-	-	-			*DISPL THLD (1700.	0 FT)
AMOME	432854.11N/1141626.95W	Υ	FO	DF	-	1.96			CG 420 FT/NM TO 6	6200
SIRPE	431943.14N/1141308.20W	Υ	FB	TF	165.25	09.49	AT/ABOVE 8400			
SIRPE	431943.14N/1141308.20W	Y	-	IF	-	-	AT/ABOVE 8400		AUREL4.PRESN	N
PRESN	431223.15N/1141854.14W	Υ	FB	TF	209.91	08.46	AT/ABOVE 8600			
SIRPE	431943.14N/1141308.20W	Υ	-	IF	-	-	AT/ABOVE 8400		AUREL4.REAPS	5
REAPS	430947.53N/1140534.46W	Υ	FB	TF	150.84	11.36	AT/ABOVE 9500			
SIRPE	431943.14N/1141308.20W	Υ	-	IF	-	-	AT/ABOVE 8400		AUREL4.SOLDE	=
SOLDE	431523.20N/1143428.57W	Υ	FB	TF	254.59	16.18				