

Print

Project Name: ROW RNAV (GPS) RWY 17

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-15 16:10:10.312302

Status: Verified

!FDC 6/3511 ROW IAP ROSWELL AIR CENTER, ROSWELL, NM. RNAV (GPS) RWY 17, ORIG-B... LNAV CAT C VISIBILITY 1 3/8. CIRCLING CATS A/B VISIBILITY 1. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ATS ALTIMETER SETTING: INCREASE LPV DA TO 3996 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 4083 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CAT D 1/4 SM. CHANGE VDP AND BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING ATS ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEM, LNAV/VNAV NA BELOW -22C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 17, ORIG-C. 2604151610-PERM

Digitally signed by
CASEY D HILL
Apr 16, 2026

