

[Print](#)

Project Name: MIV

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-01 20:06:23.283343

Status: Verified

!FDC 6/9741 MIV IAP MILLVILLE MUNI, MILLVILLE, NJ. RNAV (GPS) RWY 28, ORIG-D... LNAV AND CIRCLING CAT C VISIBILITY 1 5/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ACY ALTIMETER SETTING: INCREASE LPV DA TO 400 FEET; INCREASE LNAV/VNAV DA TO 461 FEET; INCREASE ALL MDAS 60 FEET AND LNAV AND CIRCLING VISIBILITY CAT C 1/8 SM. CHANGE VDP AND BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING ACY ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 28, ORIG-E. 2604012006-PERM

Digitally signed by

CASEY D HILL

Apr 10, 2026

