

WAAS CH 56608 W09A	APP CRS 094°	Rwy Ldg TDZE Apt Elev 9501 1016 1027
--	------------------------	--

RNAV (GPS) Y RWY 9

KANSAS CITY INTL (MCI)

RNP APCH - GPS.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV N/A below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500, and increase LNAV Cats C/D visibility to 1 3⁄8 SM. *RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 4000 direct DUSTN and on track 092° to LYMES and hold.

D-ATIS 128.375	KANSAS CITY APP CON 120.95 318.1	INTERNATIONAL TOWER 128.2 254.25	GND CON 121.8
--------------------------	--	--	-------------------------

WOOKE		4000	DUSTN	LYMES
4000		2900	tr 092°	△
GP 3.00° TCH 56		1.3 NM to RW09	RW09	
3.5 NM		4.5 NM	1.3 NM	
CATEGORY	A	B	C	D
LPV DA*	1216/24		200 (200-½)	
LNAV/VNAV DA	1336/24		320 (400-½)	
LNAV MDA	1480/24	464 (500-½)	1480/50	464 (500-1)
CIRCLING	1560-1	533 (600-1)	1560-1½ 533 (600-1½)	1580-2 553 (600-2)

ELEV 1027 D TDZE 1016

KANSAS CITY, MISSOURI

Amtd 5 FIG

39°18'N-94°43'W

KANSAS CITY INTL (MCI)

RNAV (GPS) Y RWY 9