

Print

Project Name: JHW RNAV (GPS) RWY 25

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-25 18:46:22.00721

Status: Verified

IFDC 6/6469 JHW IAP CHAUTAUQUA COUNTY/JAMESTOWN, JAMESTOWN, NY. RNAV (GPS) RWY 25, AMDT 1D... LNAV CAT C VISIBILITY 5/8. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.05 NM TO RW25. CHANGE MIN ALT AT DIPRE TO READ: DIPRE/2.10 NM TO RW25 2440. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DKK ALTIMETER SETTING: INCREASE LPV DA TO 2116 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 2249 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 200 FEET AND LNAV VISIBILITY CAT C 5/8 SM, LNAV VISIBILITY CAT D 1/4 SM, AND CIRCLING VISIBILITY CATS C/D 3/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING DKK ALTIMETER SETTING. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 SM AND LNAV CAT C TO 1 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LNAV CAT D. DELETE FOR INOPERATIVE MALSR, WHEN USING DUNKIRK ALTIMETER SETTING NOTE. THIS IS RNAV (GPS) RWY 25, AMDT 1E. 2603251846-PERM

Digitally signed by
CASEY D HILL
Apr 02, 2026

