

Print

Project Name: TOL RNAV (GPS) RWY 25

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-21 12:23:15.904911

Status: Verified

!FDC 6/5616 TOL IAP EUGENE F KRANZ TOLEDO EXPRESS, TOLEDO, OH. RNAV (GPS) RWY 25, AMDT 2D... LNAV CAT C VISIBILITY RVR 3500. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 0.96 NM TO RW25. CHANGE MIN ALT AT RIYOS TO READ: RIYOS/1.80 NM TO RW25 1280. CHANGE FOR INOPERATIVE ALS NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LPV CAT E VISIBILITY TO RVR 4000, LNAV/VNAV ALL CATS TO RVR 6000, AND LNAV CATS C/D/E TO RVR 5500. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 25, AMDT 2E. 2604211223-PERM

Digitally signed by
CASEY D HILL
Apr 27, 2026

