

Print

Project Name: AXH

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-03 19:31:20.18955

Status: Verified

!FDC 6/3957 AXH IAP HOUSTON/SOUTHWEST, HOUSTON, TX. RNAV (GPS) RWY 27, AMDT 1A... TDZE 68. LPV DA 368. LNAV/VNAV DA 605. LNAV HAT 492. LNAV CAT C VISIBILITY 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOU ALTIMETER SETTING: INCREASE LPV DA TO 402 FEET; INCREASE LNAV/VNAV DA TO 639 FEET; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C 1/8 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING HOU ALTIMETER SETTING. DELETE PLANVIEW NOTE: RADAR REQUIRED. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 27, AMDT 1B. 2603031931-PERM

Digitally signed by
CASEY D HILL
Mar 05, 2026

