

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>						<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
HEKIS						ONE	HEKIS1.HEKIS	NONE		
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>					
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>					

DP ROUTE DESCRIPTION:

VFR SEGMENT: VFR CLIMB TO MAHUT, CROSS MAHUT AT OR ABOVE 900 ON TRACK 279.34.
IFR SEGMENT: FROM MAHUT, CLIMB ON TRACK 230.32 TO HEKIS, CROSS HEKIS AT OR ABOVE 4000.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>

PBN REQUIREMENT NOTES:

RNP 0.3 - GPS. AP.

EQUIPMENT REQUIREMENT NOTES:

PROCEDURAL DATA NOTES:

NOTE: PILOT MUST ENSURE CDI SENSITIVITY IS SET TO 0.30 NM. CDI MAY BE RESET TO 1.00 NM AFTER HEKIS.
NOTE: USE OF CALAIS RGNL REQUIRES PERMISSION OF THE OWNER; USE OF THIS PROCEDURE REQUIRES SPECIFIC AUTHORIZATION BY FAA FLIGHT STANDARDS.
NOTE: USE PNN ALTIMETER SETTING; WHEN NOT RECEIVED, USE BHB ALTIMETER SETTING AND CROSS MAHUT AT OR ABOVE 1020.

TAKEOFF MINIMUMS:

TAKEOFF OBSTACLES NOTES:

CONTROLLING OBSTACLES:

IDF ALTITUDE CONTROLLING OBSTACLE: 368 AAO 451024.00N/0671712.00W.
IFR SEGMENT CONTROLLING OBSTACLE: 628 TOWER (23-080488) 450931.07N/0671649.76W.
MSA CONTROLLING OBSTACLE: 302 TOWER (23-000357) 452318.19N/0674750.08W.

MSA:

MSA FROM MAHUT, 2600 WITHIN A 25 NM RADIUS.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: NOT CONDUCTED.
HELIPORT MV: 46ME 16W/2025.
CHART: TOP ALTITUDE: ASSIGNED BY ATC.
CHART PNN AWOS-AV.
CHART KPNN.



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
HEKIS	ONE	HEKIS1.HEKIS	NONE		

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
46ME	CALAIS	ME

COMMUNICATIONS:

BGR FSS, ZBW ARTCC.

FIXES AND/OR NAVAIDS:

REMARKS:

RASS PRESSURE PATTERNS THE SAME.
46ME: 153, KPNN: 265, KBHB: 83
RA=43.00
PNN AWOS IS NOT ON WMSCR
46ME DOES NOT HAVE A LOCAL ALTIMETER.
100 FT VEGETATION HEIGHT USED.
FIX HEKIS IS ON SPECIAL COPTER ROUTE ZK420.
POC: LIFEFLIGHT OF MAINE- DAVID BURR: 207-462-3622, CALAIS RGNL HOSPITAL: 207-454-7521 ROD TIRRELL 207-454-9231.
FLIGHT INTO CANADIAN AIRSPACE HAS BEEN COORDINATED THROUGH BOSTON ARTCC AND MONCTON ACC. POC: MICHAEL OXNER (NAV CANADA) 506-867-7178.

BLANKET WAIVERS ON FILE (2):
AFS-400 MEMO DATED 01/26/24, SUBJECT: WAIVER TO INSTRUMENT PROCEDURE DESIGN INITIAL DEPARTURE FIX CRITERIA.
AFS-400 MEMO DATED 01/12/24, SUBJECT: WAIVER TO SIGNATURES ON SPECIAL INSTRUMENT FLIGHT PROCEDURE FORMS.

FLIGHT INSPECTED BY

TERRY HESTER

SIGNATURE

Digitally signed by

RAKE MCGRAW

OFFICE

AJF

DATE

04/23/2025

May 14, 2025

Digitally signed by

RAKE MCGRAW

OFFICE

AJV-A422

DATE

12/05/2024

May 14, 2025

DEVELOPED BY

RALPH DUMAR

SIGNATURE

APPROVED BY

BEV L BORDY

SIGNATURE

Digitally signed by

RAKE MCGRAW

OFFICE

AJV-A420

DATE

May 14, 2025

TITLE

MANAGER

REQUIRED EFFECTIVE DATE

COORDINATED WITH:

A4A ☐ **ALPA** ☐ **AOPA** ☐ **APA** ☐ **HAI** ☒ **NBAA** ☐ **OTHER:**ZBW ARTCC, ARPT MGR, LIFEFLIGHT OF MAINE AVIATION SERVICES LLC

CHANGES - REASONS:

ORIGINAL PROCEDURE - REQUESTED BY FPT, ATC AND APT MGR.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>							<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
HEKIS							ONE	HEKIS1.HEKIS	NONE		
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>		
46ME	451037.69N/0671604.57W	N	-	-	-	-			VFR SEGMENT		
900 MSL	-	-	-	-	-	-					
MAHUT	451033.17N/0671659.39W	Y	FB	IF	-	-	AT/ABOVE 900		IFR SEGMENT		
HEKIS	450538.97N/0672142.80W	Y	FB	TF	214.32	5.94	AT/ABOVE 4000				

