

[Print](#)

Project Name: SWO

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-20 18:02:29.521229

Status: Verified

IFDC 6/4924 SWO IAP STILLWATER RGNL, STILLWATER, OK. VOR RWY 17, AMDT 14A... S-17 CAT C VISIBILITY 7/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PNC ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET AND S-17 VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CAT D 1/2 SM. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING PNC ALTIMETER SETTING. CHANGE HELICOPTER VISIBILITY REDUCTION NOTE TO READ: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE S-17 CATS A/B VISIBILITY TO 1 SM AND S-17 CAT D TO 1 3/8 SM. THIS IS VOR RWY 17, AMDT 14B. 2604201802-PERM

Digitally signed by

CASEY D HILL

Apr 24, 2026

