

WAAS CH 99415 W09A	APP CRS 093°	Rwy Idg 5003 TDZE 8 APT Elev 10
--	------------------------	--

RNAV (GPS) RWY 9L

MIAMI EXEC (KTMB)

RNP APCH - GPS.				MISSED APPROACH: CLIMB TO 2000 DIRECT HOTMA AND HOLD.
CIRCLING RWY 13 NA AT NIGHT. BARO-VNAV NA WHEN USING MIA ALTIMETER SETTING. FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15°C OR ABOVE 54°C. SIMULTANEOUS APPROACH AUTHORIZED. LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS. USE OF FD OR AP REQUIRED DURING SIMULTANEOUS OPERATIONS. WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MIA ALTIMETER SETTING AND INCREASE LPV DA TO 283 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE LNAV/VNAV DA TO 290 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE ALL MDAS 40 FEET AND LNAV CATS C/D VISIBILITY 1/8 SM.				
ATIS 124.0	MIAMI APP CON 125.5 354.1	MIAMI EXEC TOWER 118.9 (CTAF)	GND CON 121.7	CLNC DEL 133.0

PROTOTYPE-NOT FOR NAVIGATION

