

Print

Project Name: CQA

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-02-27 12:59:14.555554

Status: Verified

!FDC 6/3363 CQA IAP LAKEFIELD, CELINA, OH. RNAV (GPS) RWY 8, ORIG-B... LNAV CAT C VISIBILITY 1 5/8. CHANGE ALTIMETER NOTE TO READ: USE AXV ALTIMETER SETTING; WHEN NOT RECEIVED, USE DAY ALTIMETER SETTING AND INCREASE LPV DA TO 1293 FEET; INCREASE LNAV/VNAV DA TO 1350 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE HELICOPTER VISIBILITY REDUCTION NOTE TO READ: RWY 8 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 8, ORIG-C. 2602271259-PERM



Digitally signed by  
**CASEY D HILL**  
Mar 04, 2026