

[Print](#)

Project Name: ONL RNAV (GPS) RWY 31

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-10 13:00:31.348773

Status: Verified

!FDC 6/2217 ONL IAP THE O'NEILL MUNI-JOHN L BAKER FLD, O'NEILL, NE. RNAV (GPS) RWY 31, AMDT 1C... LNAV/VNAV ALL CATS DA/HAT 2580/548. LNAV CAT C VISIBILITY 1 5/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ODX ALTIMETER SETTING: INCREASE LPV DA TO 2407 FEET; INCREASE LNAV/VNAV DA TO 2705 FEET; INCREASE ALL MDAS 140 FEET AND LNAV VISIBILITY CAT C 3/8 SM AND CIRCLING VISIBILITY CAT C 1/2 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING ODX ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C OR ABOVE 54C. CHANGE HELICOPTER VISIBILITY REDUCTION NOTE TO READ: RWY 31 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE NIGHT LANDING NOTE TO READ: CIRCLING RWY 4, 22 NA AT NIGHT. THIS IS RNAV (GPS) RWY 31, AMDT 1D. 2604101300-PERM

Digitally signed by

CASEY D HILL

Apr 14, 2026

