

Print

Project Name: IXD

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-23 19:32:31.477048

Status: Verified

!FDC 6/3468 IXD IAP NEW CENTURY AIRCENTER, OLATHE, KS. RNAV (GPS) RWY 36, AMDT 2A... LNAV CAT C VISIBILITY 5/8. DELETE LNAV/VNAV MINIMUMS. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.05 NM TO RW36. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LNAV CAT C VISIBILITY TO 1 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LNAV CAT D. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OJC ALTIMETER SETTING: INCREASE LPV DA TO 1335 FEET; INCREASE ALL MDAS 20 FEET. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING OJC ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 36, AMDT 2B. 2603231932-PERM

Digitally signed by
CASEY D HILL
Mar 26, 2026

