

[Print](#)

Project Name: DRT

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-06 17:03:14.443601

Status: Verified

!FDC 6/6676 DRT IAP DEL RIO INTL, DEL RIO, TX. RNAV (GPS) RWY 13, AMDT 2B... LNAV CATS A/B VISIBILITY 3/4, CATS C/D 1 1/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT HIBUD TO READ: HIBUD/1.90 NM TO RW13 1640. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 1/8 SM. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DLF ALTIMETER SETTING: INCREASE LPV DA TO 1282 FEET; INCREASE LNAV/VNAV DA TO 1431 FEET; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CATS C/D 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING DLF ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. DELETE VGSI AND RNAV GLIDEPATH NOT COINCIDENT NOTE. THIS IS RNAV (GPS) RWY 13, AMDT 2C. 2603061703-PERM

Digitally signed by

CASEY D HILL

Mar 16, 2026

