

Flight Procedures Cover Page	Task Action: FLIGHT CHECK	Task Type: IAP	Estimated Chart Date: 09/03/2026	APWS Task ID: F7A5E02174AE4E22B5DFEA39678E2DC1	APWS Project ID: 96740957E01A4DFC9D7921EE14860C36
Procedure: RNAV (GPS) RWY 32 AMDT 5		Enroute: NO	Specialist: Kenney, Taylor		Agreement Number:
Airport ID: KTBR			Airport City: STATESBORO		State: GA
Facility ID:	Facility Type:	Flight Inspection Remark Type: New FC Slot			
Procedure Comments: ACTIVE AIRNAV DATA USED. POC: ROB HAMILTON, AJV-A433, (405) 954-4608. QUALITY 29 CHECKED QUALITY 39 CHECKED					

FIPC BASIC FORM							
PROCEDURE: RNAV (GPS) RWY 32 AMDT 5			AIRPORT NAME: STATESBORO-BULLOCH COUNTY		AIRPORT ID: KTBR	SPECIAL CONTROL NO: AG-05-027-26	
FAC ID: KTBR32.05		CITY: STATESBORO			ST: GA	ORIG CHART DATE: 09/03/2026	
DFL TYPE: PROC/S	THIRD PARTY: ☐ YES	EST. TIME ON SITE: 0.4	REIMB. NUMBER:		PTS TASK ID: F7A5E02174AE4E22B5DFEA39678E2DC1		
PREFLIGHT NOTES							
REVIEWER:					DATE:		
COMMENTS:					CHECK ONE:		
					☐ FLT CK REQ ☐ NFCR ☐ REJECT		
							YES
					CPV COMPLETE?		X
PROCEDURE RESULTS							
INSPECTION DATE: 06/05/2026		CREW #: VN586	N #: N69	INSTRUMENT PROCEDURE STATUS: ☒ SAT ☐ SAT W/CHANGES ☐ UNSAT		ARINC CODING: ☒ SAT ☐ SAT/GOLD ☐ UNSAT	
FLIGHT INSPECTOR SIGNATURE: adam k stalvey @ 06/05/2026 12:39			PRINTED NAME: STALVEY, ADAM KEITH				NOTAM INITIATED? ☐ YES ☒ NO
FLIGHT INSPECTOR REMARKS: Statesboro-Bulloch County, Statesboro, GA, RNAV (GPS) RWY 32, Amdt 5, SAT.							
IN-FLIGHT OBSTACLE REPORT							
OBSTRUCTION ID #:	COORDINATES OR LOCATION:		GNSS ALTITUDE (MSL):		BAROMETRIC ALTITUDE (MSL):		HEIGHT ABOVE GROUND LEVEL:

WAAS
CH 81829
W32A

APP CRS
320°

Rwy Ldg
TDZE
Apt Elev

5701
179
187

EXISTING

RNAV (GPS) RWY 32

STATESBORO-BULLOCH COUNTY (TBR)

RNP APCH-GPS.
⚠ Circling to Rwy 6/24 NA at night. Baro-VNAV NA when using Sylvania altimeter setting.
⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.
For inop ALS. Increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cats C/D to 1½ SM.
When local altimeter setting not received. Use Sylvania altimeter setting and increase LPV DA to 408 feet; increase LNAV/VNAV DA to 490 feet; increase all MDAs 40 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C ¼ SM. For inop ALS when using Sylvania altimeter setting, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat C/D to 1½ SM.

MALSR
A5

MISSED APPROACH:
Climb to 2600 direct
EPEDE and hold.

AWOS-3 119.025	SAVANNAH APP CON ★ 118.4 307.225	UNICOM 122.725 (CTAF) 0
-------------------	-------------------------------------	----------------------------

