

[Print](#)

Project Name: MPE

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-08 15:40:11.225418

Status: Verified

!FDC 6/0965 MPE IAP PHILADELPHIA MUNI, PHILADELPHIA, MS. RNAV (GPS) RWY 36, AMDT 1A... LNAV/VNAV ALL CATS DA/HAT 1040/582. LNAV CAT C VISIBILITY 1 3/4. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE \*LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.70 NM TO RW36. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MEI ALTIMETER SETTING: INCREASE LPV DA TO 940 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1142 FEET; INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CATS C/D 1/4 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING MEI ALTIMETER SETTING. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NA NOTE TO READ: RWY 36 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 36, AMDT 1B. 2604081540-PERM

*Digitally signed by*

**CASEY D HILL**

Apr 14, 2026

