

[Print](#)

Project Name: PABL

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-24 13:00:59.754363

Status: Verified

!FDC 6/1411 BVK IAP BUCKLAND, BUCKLAND, AK. RNAV (GPS) RWY 29, AMDT 1... LP CAT C VISIBILITY 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WLK/PASK ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET AND LP AND LNAV VISIBILITY CAT C 3/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING WLK/PASK ALTIMETER SETTING. CHANGE CHART VDP TO READ: CHART VDP AT 1.21 NM TO RW29. THIS IS RNAV (GPS) RWY 29, AMDT 1A. 2604241300-PERM

Digitally signed by

CASEY D HILL

May 04, 2026

